



TUONO 457 - TECHNICAL SPECIFICATION

Engine	Parallel twin, 4 valves per cylinder, liquid-cooled with Ride-By-Wire
Displacement	457 cc
Bore x stroke	69 x 61.1 mm
Max. power	47.6 HP (35 kW) @ 9,400 rpm
Max. Torque	43.5 Nm @ 6,700 rpm
Clutch	Multi plate wet clutch with slipper system
Gearbox	6 speed
Frame	Twin spar aluminum frame
Front suspension	Ø 41mm USD fork, adjustable preload, 120mm wheel travel
Rear suspension	Monoshock, adjustable preload, 130 mm wheel travel
Front brake	Ø 320 mm floating disc. ByBre 4-piston radial caliper
Rear brake	Ø 220 mm disc. ByBre caliper
Front wheel	Cast wheels 17" x 3"
Rear wheel	Cast wheels 17" x 4.5"
Seat height	800 mm
Fuel tank capacity	12.7 litres
Wet weight*	175 Kg
Standard Features	Full LED headlights and indicators. 5" TFT dashboard. Backlit switch cubes. Engine Maps (AEM), Dual-Channel ABS with Anti Roll-Over System (2 maps), Traction Control (ATC), 3 Riding Modes. Metal Braided Brake Hoses

**According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fueled with at least 90% of usable tank volume*