

DORSODURO 900 - TECHNICAL SPECIFICATIONS

ENGINE	Aprilia 90° V-Twin, 4-stroke, four valves per cylinder,
	liquid cooled. Ride-by-Wire system with 3 engine maps
DISPLACEMENT	896.1 cc
MAX. POWER AT CRANKSHAFT	95 HP (70 kW) at 8,750 rpm
MAX. TORQUE AT CRANKSHAFT	90 Nm at 6,500 rpm
FRONT SUSPENSION	Kayaba upside-down fork, Ø 41 mm stanchions
	adjustable in preload and hydraulic rebound damping
	Wheel travel: 160 mm
REAR SUSPENSION	Aluminium alloy swingarm
	Sachs monoshock absorber adjustable in preload
	and hydraulic rebound damping. Wheel travel: 155 mm
FRONT BRAKE	Ø 320 mm floating double disc with aluminium flange. Metal braid brake pipe.
	Radial callipers with four pistons. ABS Continental
REAR BRAKE	Ø 240 mm wave stainless steel disc. Single piston calliper
	Metal braid brake pipe. ABS Continental
FRONT WHEEL	3-spoke 3.5" x 17" aluminium alloy wheel.
	Tyre: 120/70 ZR 17"
REAR WHEEL	3-spoke 6" x 17" aluminium alloy wheel.
	Tyre: 180/55 ZR 17"
SADDLE HEIGHT	870 mm
FUEL TANK CAPACITY	12 lt
DRY WEIGHT	195 kg
WET WEIGHT	212 kg
EMISSIONS COMPLIANCE	Euro 4
EMISSIONS	131 g/km (CO2)
CONSUMPTION	5.6 l/100km
ELECTRONIC MANAGEMENT	Traction control, Aprilia Mia (multimedia platform) predisposition.
COLOUR RANGE	Adrenalininc Silver, Exciting Dark
ACCESSORIES	Gel comfort seat, Racing levers, rider footpegs rubber cover, aluminium rear mirror, led flasher, clutch and brake oil tank cap, sporty slip on