



## TECHNICAL SPECIFICATION

<b>Engine</b>	Single-cylinder 4-stroke i-get with Start&Stop system
<b>Cooling</b>	Liquid-cooled
<b>Displacement</b>	174 cc
<b>Maximum power</b>	13 kW (17,4HP) at 8,500 rpm
<b>Maximum torque</b>	16.5 Nm at 7,000 rpm
<b>Chassis</b>	Double cradle, in high-resistance steel tubing
<b>Gearbox</b>	Continuously variable transmission (CVT)
<b>Front suspension</b>	Showa hydraulic telescopic fork Ø 33 mm (120 mm travel)
<b>Rear suspension</b>	Showa double hydraulic shock absorber with adjustable preload (102 mm travel)
<b>Front brake</b>	Hydraulic with wave disc, Ø 260 mm - ABS
<b>Rear brake</b>	Hydraulic with wave disc, Ø 220 mm
<b>Front wheel</b>	Tubless 110/80 - 14"
<b>Rear wheel</b>	Tubless 130/70 - 13"
<b>Dimensions (LxWxH)</b>	1920 mm x 765 mm x 1295 mm
<b>Seat height.</b>	799 mm.
<b>Fuel tank capacity</b>	9l
<b>Wet weight</b>	148 Kg
<b>Fuel Consumption</b>	2,6 l/100 km
<b>Emission Compliance</b>	Euro 3 (Euro 5 standard in Europe)